



FUNI ACCIAIO ZINCATO ANTIGIRO

ZMP 247 ANTIGIRO	Ø FUNE	FILO EXT.	PESO	CARICO ROTTURA min.		
168 fili – 24x7 Parallela DX – Res. 2.160 N/mm ²	mm.	mm.	Kg/m.	Kgf.	kN	
	7	0,45	0,210	4.430	43,43	
	7,2	0,47	0,220	4.350	42,65	
	8	0,52	0,280	5.650	55,39	
	9	0,57	0,350	7.000	68,63	
	10	0,62	0,430	8.600	84,31	
	11	0,70	0,510	10.027	98,30	
	12	0,77	0,600	12.300	120,59	
	12,5	0,80	0,650	13.260	130,00	
	13	0,82	0,710	13.660	133,92	
	14	0,90	0,820	16.200	158,82	
	15	0,98	0,940	18.150	177,94	
	16	1,03	1,060	20.500	200,98	
	17	1,10	1,210	23.150	226,96	
	18	1,15	1,370	26.600	260,78	
	19	1,23	1,500	28.978	284,10	
	20	1,27	1,650	31.936	313,10	

ZMP 247 CT ANTIGIRO	Ø FUNE	FILO EXT.	PESO	CARICO ROTTURA min.		
168 fili – 24x7 – Trefoli Trafilati Parallela DX – Res. 2.160 N/mm ²	mm.	mm.	Kg/m.	Kgf.	kN	
	7	0,45	0,230	4.510	44,22	
	8	0,52	0,290	6.100	59,80	
	9	0,60	0,360	7.344	72,00	
	9,2	0,65	0,400	8.010	78,53	
	10	0,68	0,460	9.000	88,24	
	11	0,75	0,570	11.100	108,82	
	12	0,82	0,680	13.350	130,88	
	13	0,89	0,780	15.200	149,02	
	14	0,95	0,910	17.900	175,49	
	15	1,01	1,040	20.900	204,90	
	16	1,08	1,210	23.500	230,39	
	18	1,20	1,550	30.090	295,00	
	19	1,29	1,700	33.050	324,02	
	20	1,33	1,860	36.108	354,00	
	22	1,46	2,270	44.070	432,06	
	24	1,60	2,740	52.940	519,02	