



ZM 357 R CT ANTIGIRO	Ø FUNE	FILO EXT.	PESO	CARICO ROTTURA min.	
259 fili – 35x7 – Trefoli Trafilati Parallela DX – Res. 2.160 N/mm ²	mm.	mm.	Kg/m.	Kgf.	kN
	8	0,43	0,330	6.500	63,73
	10	0,54	0,480	9.580	93,92
	11	0,57	0,580	11.480	112,55
	12	0,60	0,660	14.280	140,00
	13	0,63	0,810	17.150	168,14
	14	0,66	0,910	19.100	187,25
	15	0,73	1,080	22.850	224,02
	16	0,77	1,200	26.010	255,00
	17	0,83	1,350	28.350	277,94
	18	0,87	1,530	31.400	307,84
	19	0,95	1,640	35.600	349,02
	20	0,97	1,910	38.980	382,16
	21	1,00	2,050	44.100	432,35
	22	1,05	2,240	48.050	471,08
	24	1,15	2,680	56.200	550,98
	26	1,25	3,070	65.300	640,20
	28	1,35	3,800	76.300	748,04
	30	1,45	4,190	87.500	857,84
	32	1,55	4,770	101.500	995,10
	34	1,65	5,380	112.400	1101,96
	36	1,75	5,807	125.970	1235,00
	38	1,85	7,010	133.000	1303,92

ZM 357 R CT ANT.PLAST.	Ø FUNE	FILO EXT.	PESO	CARICO ROTTURA min.	
259 fili – 35x7 – Trefoli Trafilati Parallela DX – Res. 2.160 N/mm ² ANIMA PLAST	mm.	mm.	Kg/m.	Kgf.	kN
	20	0,97	1,910	38.980	382,16
	21	1,00	2,050	44.100	432,35
	22	1,05	2,240	48.050	471,08
	23	1,09	2,510	53.015	519,75
	24	1,15	2,680	56.200	550,98
	25	1,18	2,780	62.100	608,82
	26	1,25	3,070	65.300	640,20
	27	1,29	3,540	69.100	677,45
	28	1,35	3,800	76.300	748,04
	30	1,45	4,190	87.500	857,84
	32	1,55	4,770	101.500	995,10
	34	1,65	5,380	112.400	1.101,96
	36	1,75	5,807	125.970	1.235,00
	38	1,85	7,010	133.000	1.303,92